



Aerolite® Soft Touch

Glasswool: thermal and acoustic ceiling insulation





Aerolite® Soft Touch is a high performance Glasswool thermal and acoustic ceiling insulation that keeps you warm in winter and cool in summer.

TECHNICAL DATA SHEET



**BETTER INSULATION
= GREATER SAVINGS**



**DOES NOT BURN
OR SPREAD FIRE**



**SOFTER AND SIMPLER
TO INSTALL**



**ENVIRONMENTALLY FRIENDLY
RECYCLED GLASS**



**COMPRESSED ROLL,
SAME GREAT COVERAGE**

DESCRIPTION

Aerolite® Soft Touch is a high performance Glasswool thermal and acoustic ceiling insulation that is bonded with an inert, thermosetting resin. The strong, resilient, flexible blankets are supplied in compression packed rolls and are easy to cut and install.

QUALITY MANAGEMENT SYSTEM

Isover products are manufactured according to ISO 9001:2015.

ENVIRONMENTAL SUSTAINABILITY

Isover products are manufactured according to ISO 14001:2015.

Less material, less energy and less emissions

- Zero ozone depleting potential (ODP)
- Zero global warming potential (GWP).

FEATURES & BENEFITS

- Energy saving
- Lightweight and easy to install
- Exceptional thermal and acoustic properties
- Safe application and use
- Maintenance free
- Long product life - will not readily age
- SABS mark (SABS 1381 part 1)
- Compression packed to reduce volume and optimise transport and storage
- Recovers to full thickness within 24-48 hrs.

FIRE PROPERTIES

- No smoke/ toxic fumes
- Non-combustible – tested to SANS 10177 Part 5
- SANS 428 fire classification – A/A1/1
- EN 13501 fire classification – A1-s1, d0

THERMAL PROPERTIES

Contributes to indoor comfort and lifelong savings by reducing heat loss/gain due to its inherent thermal insulation properties.

ACOUSTIC PROPERTIES

Offers exceptional acoustic properties and enhances indoor environmental quality by reducing the transference of noise. Aerolite® Soft Touch ceiling insulation reduces the sound transmission to and from a room.

APPLICATIONS

Ceiling insulation in:

- Residential buildings
- Retro-fit in existing homes
- Top up insulation
- Non-residential buildings.

DURABILITY

- Odourless, inert and fully compatible with all standard building materials and components
- Will not promote corrosion of steel, copper or aluminium
- Will not breed or promote fungi, mould or bacteria
- Non-hygroscopic
- Dust settlement will not hamper the product's performance.

PHYSICAL PROPERTIES

R-value (m ² .K/W)	Thickness (mm)	Length (mm)	Width (mm)	Density (kg/m ³)	K-value (W/m.K) per roll	Pack Volume (m ³)	NRC
1.14	50	10 000	1 200	10	0.044	0.191	0.80
2.50	100	6 000	1 200	11	0.040	0.211	1.00
3.38	135	5 000	1 200	11	0.040	0.211	1.10

Aerolite® Soft Touch 50 mm can be installed as top-up in homes that already have insulation but do not meet the stipulated minimum requirements for new buildings in SANS 10400-XA.

TOOLS NEEDED FOR INSTALLATION

A sharp knife or wood saw, tape measure and a balancing plank (to prevent ceiling damage).

INSTALLATION INSTRUCTIONS

1. Measure the distance between the timber roof trusses.
2. Cut the Aerolite® Soft Touch while still in the bag to the correct width to snugly fit the space between the roof trusses.
3. Roll out the Aerolite® Soft Touch between the roof trusses on top of the ceiling.
4. It is advisable to lay the Aerolite® Soft Touch underneath any wiring and to cut around any down lights to prevent overheating of light fitting.
5. Wrap off-cuts around pipes to prevent them freezing in winter.

WARNING: Be careful not to step onto the ceiling board as you may damage the board or fall through the ceiling.

HANDLING & STORAGE

Store product under cover and in dry conditions. Store flat. Handle with care, especially on the edges and corners, which can be damaged if subject to sharp or heavy impact. Do not apply excessive pressure, for example by standing or sitting on the product, as permanent damage may be caused.

ARCHITECTURAL SPECIFICATION

Install (50/100/135) mm thick flexible non-combustible lightweight "Aerolite® Soft Touch" insulation material between the roof trusses and over bracing in a completed roof and ceiling system. Installation strictly in accordance with the manufacturer's detail and specification.



Isover is a division of Saint-Gobain Construction Products SA (Pty) Ltd
Block A • Siemens Office Park
• 300 Janadel Avenue • Halfway House
• Midrand • 1685
PO Box 50416 • Randjiesfontein
• 1683 • South Africa
+27 (0)12 657 2800
www.isover.co.za



Isover reserves the right to alter or amend product specification without notice. The information given in this publication is correct to the best of our knowledge at the time of publication. Whilst Isover will endeavour to ensure publications are up to date, it is the users' responsibility to check with us that it is correct prior to use.

Tel: 0860 ISOVER (476837)

www.isover.co.za/products/aerolite-soft-touch