



Geyser Insulation Pack

Glasswool: An energy conservation solution for geyser systems

DESCRIPTION

The Isover Geyser Insulation pack consists of a foil faced Glasswool insulation blanket in a kit form that includes 5 x 1 m, high density Glasswool Snap On Pipe insulation of 15 mm ID bore x 20 mm wall thickness and duct tape. Additional pipe insulation available on request.

QUALITY MANAGEMENT SYSTEM

Isover products are manufactured according to ISO 9001:2008.

ENVIRONMENTAL SUSTAINABILITY

Isover products are manufactured according to ISO 14001:2004.

Less material, less energy and less emissions

- Zero ozone depleting potential (ODP)
- Zero global warming potential (GWP)

FEATURES & BENEFITS

- Lifelong energy savings
- Lightweight and easy to handle
- DIY friendly
- Maintenance free
- Long product life - will not readily age
- Suitable for high humidity applications

FIRE PROPERTIES

Geyser blanket:

- Non-combustible - tested to SANS 10177 Part 5
- Class 1 fire index rating - tested to SANS 10177 Part 3
- Class A1, s1, do according to EN 13823
- Tested to ASTM E-84
 - Flame Spread Index: 20
 - Smoke Development Index: 5

Pipes:

- Class 1 fire index rating - tested to SANS 10177 Part 3

THERMAL PROPERTIES

Contributes to lifelong savings by reducing heat loss through the geyser and associated piping due to the inherent thermal insulation properties.

APPLICATIONS

Geyser and pipe insulation for:

- Domestic
- Commercial
- Public sector buildings

DURABILITY

- Odourless, inert and fully compatible with all standard building materials and components
- Will not promote corrosion of steel, copper or aluminium
- Will not sustain vermin
- Will not breed or promote fungi, mould or bacteria
- Non-hygroscopic



Geyser Insulation Pack



PHYSICAL PROPERTIES

Product	Rval (m ² .K/W)	Dimensions (mm)	Density	k-value (W/m.K)	Qty / pack
Foil Faced Glasswool Blanket	1.28	3500 x 1200 x 50	12 kg/m ³	0.039	1 roll
Glasswool Snap on Pipe insulation	1.00	15 x 35	88 kg/m ³	0.033	5 metres

Typical values

TOOLS NEEDED FOR INSTALLATION

A sharp blade may be needed for cutting.

INSTALLATION INSTRUCTIONS

1. Wrap the entire geyser - ensure the foil is facing the outside.
2. Secure the blanket with the binding tape supplied and cut off excess.
3. Close the ends and tape down.
4. Install pipe insulation around pipes to and from the geyser (mitre cut pipe sections around bends).

HANDLING & STORAGE

Store product under cover and in dry conditions. Store flat. Handle with care, especially on the edges and corners, which can be damaged if subject to sharp or heavy impact. Do not apply excessive pressure, for example by standing or sitting on the product, as permanent damage may be caused.

ARCHITECTURAL SPECIFICATION

Install 50 mm thick, non-combustible, lightweight Glasswool "Geyser Blanket" around geyser or hot water cylinder. Seal edges with duct tape. Apply 2 m of 20 mm thick "Snap On Pipe" insulation on the incoming cold water pipes and insulate all outgoing hot water pipes.

**Geyser
Insulation
Pack**

ISOVER
SAINT-GOBAIN

Isover reserves the right to alter or amend product specification without notice. The information given in this publication is correct to the best of our knowledge at the time of publication. Whilst Isover will endeavour to ensure publications are up to date, it is the users' responsibility to check with us that it is correct prior to use.

ISOVER
SAINT-GOBAIN

Tel: 0860 ISOVER (476837) Fax: 086 673 1088
www.isover.co.za