



Factoryboard

GLASSWOOL: A RIGID FACED BOARD FOR ROOF AND WALL INSULATION

Factoryboard is a rigid, high performing thermal and acoustic insulation that is manufactured from non-combustible Glasswool.

Advantages



Energy saving



Thermal comfort



Sound insulation and absorption

Factoryboard will reduce thermal heat transmission and as a result will reduce power consumption significantly. Insulating metal buildings is essential and helps stabilise the structures interior temperature.

DESCRIPTION

Factoryboard is a rigid board manufactured from non-combustible Glasswool insulation. Available in 25, 40 or 50 mm thickness. It can be supplied with an ASTM E-84 tested reinforced foil or white metalised foil. Alternative facings are also available (white embossed vinyl or black non-woven glass tissue).

QUALITY MANAGEMENT SYSTEM

Isover products are manufactured according to ISO 9001:2008.

ENVIRONMENTAL SUSTAINABILITY

Isover products are manufactured according to ISO 14001:2004.

Less material, less energy and less emissions

- ▶ Zero ozone depleting potential (ODP)
- ▶ Zero global warming potential (GWP)

FEATURES & BENEFITS

- ▶ Excellent thermal and acoustic properties
- ▶ Maintenance free
- ▶ Long product life – will not readily age
- ▶ Significantly reduces heat loss/gain
- ▶ Made to size to reduce wastage

THERMAL PROPERTIES

Contributes to indoor comfort and lifelong savings by reducing heat loss/gain due to the inherent thermal insulation properties.

FIRE PROPERTIES

Foil / WMF:

- ▶ Class B/B1/2/H&V (SPR & UNSPR) Sans 428 Classification
- ▶ Class A2 – EN 13501 Classification

ACOUSTIC PROPERTIES

Offers exceptional acoustic properties and enhances indoor environmental quality by absorption of noise.

APPLICATIONS

- ▶ Multi-purpose wall cladding:
 - Recommended to be installed in a grid system.
- ▶ Over purlin roof insulation for new buildings or in a supporting grid system for existing buildings.
- ▶ Should not be installed in applications where the facing material is exposed to direct or indirect ultraviolet radiation.

DURABILITY

- ▶ Odourless, inert and fully compatible with all standard building materials and components
- ▶ Will not promote corrosion of steel, copper or aluminium
- ▶ Will not sustain vermin
- ▶ Will not breed or promote fungi, mould or bacteria
- ▶ Non-hygroscopic
- ▶ Dust settlement will not hamper the products performance

PHYSICAL PROPERTIES

Rval (m ² .K/W)	Thickness (mm)	Length (mm)	Width (mm)	Density (kg/m ³)	k-value (W/m.K)	NRC Value	Quantity/ Pallet
0.78	25	2400	1200	80	0.032	0.65	50 boards
1.56	50	2400	1200	80	0.032	-	28 boards

Typical values and standard product dimensions

- Lengths can be tailor-made in metric units to the nearest 100 mm
- Maximum recommended lengths: 25 mm Board - 2.8 m, and 50 mm Board - 3.2 m

TOOLS NEEDED FOR INSTALLATION

Boards are manufactured to length – a sharp knife will be required should cutting be necessary.

INSTALLATION INSTRUCTIONS

Take care when installing in windy conditions.

1. When installing over purlins, a C clip/metal saddle must be inserted through the board so that the roof sheet clip is fixed to the structure and not to the board.
2. Use H-sections or T-sections to span between the purlins to support the board along the longitudinal joint. Minimum recommended face width of T or H-section – 35 mm.

HANDLING & STORAGE

Store product under cover and in dry conditions. Store flat. Handle with care, especially on the edges and corners, which can be damaged if subject to sharp or heavy impact. Do not apply excessive pressure, for example by standing or sitting on the product, as permanent damage may be caused.

3. For retro-fit roof insulation installations, it is recommended that Factoryboard be installed as a ceiling in a standard suspended grid system.

ARCHITECTURAL SPECIFICATION

Install (25/50) mm thick, rigid “Factoryboard” as an aesthetic, acoustic and thermal (wall cladding/ suspended ceiling/over purlin roof insulation). Density 80 kg/m³ faced with (reinforced foil/ white metalised foil/white embossed vinyl/ black non-woven glass tissue). Install as per manufacturer’s specifications.



ISOVER is a division of Saint-Gobain Construction Products SA (Pty) Ltd
 Block A • Siemens Office Park
 • 300 Janadel Avenue • Halfway House
 • Midrand • 1685
 PO Box 50416 • Randjesfontein
 • 1683 • South Africa
 +27 (0)12 657 2800
www.isover.co.za

ISOVER reserves the right to alter or amend product specification without notice. The information given in this publication is correct to the best of our knowledge at the time of publication. Whilst Isover will endeavour to ensure publications are up to date, it is the users' responsibility to check with us that it is correct prior to use.

Tel: 0860 ISOVER (476837) **Fax:** 086 673 1088
www.isover.co.za | www.aerolite.co.za

EXAMPLE OF STANDARD SKU NAMING CONVENTION

SKU #	Material description	Facing 1/ Facing 2	Length X Width X Thickness	Density	Detail of facing/ features	Status*
17953	FAC-BRD	FOIL/WMF	2500X1200X25	-80	FE	MTO

*MTO – Make to Order / Blank – Stock item