



Sonic Liner

Glasswool: A flexible internal lining for HVAC Ducts

DESCRIPTION

Sonic Liner is a flexible Glasswool insulation blanket faced with an acoustically permeable black woven glass cloth on the air stream surface. A 35mm overlapping flange of the facing material is provided on both sides to enable effective sealing. It provides outstanding acoustical and thermal performance with low air friction.

QUALITY MANAGEMENT SYSTEM

ISOVER products are manufactured according to ISO 9001:2008.

ENVIRONMENTAL SUSTAINABILITY

ISOVER products are manufactured according to ISO 14001:2004.

Less material, less energy and less emissions

- Zero ozone depleting potential (ODP)
- Zero global warming potential (GWP)

FEATURES & BENEFITS

- Lifelong energy savings
- Excellent thermal and acoustic properties
- Maintenance free
- Minimal air friction while optimising free duct area
- Safe application and use
- The air stream will not erode or release fibres into the air stream under normal operating conditions

FIRE PROPERTIES

- Non-combustible - tested to SANS 10177-5

THERMAL PROPERTIES

Significantly reduces heat gain and loss.

ACOUSTIC PROPERTIES

Offers exceptional acoustic properties and enhances indoor environmental quality by absorption of mechanical noise generated by air conditioning equipment. Sonic Liner reduces the sound transmission along a duct.

APPLICATIONS

Specially designed as an internal acoustical insulation liner for sheet metal ducts in heating, ventilation and air conditioning systems operating at temperatures of up to 120°C and air velocities up to 20m/s.



Sonic Liner

DURABILITY

- Odourless, inert and fully compatible with all standard building materials and components
- Will not promote corrosion of steel, copper or aluminium
- Will not sustain vermin
- Will not breed or promote fungi, mould or bacteria
- Non-hygroscopic
- Prevents condensation on cold metal duct surfaces, extending the life of the system

ARCHITECTURAL SPECIFICATION

Install (25/50)mm flexible non-combustible lightweight "Sonic Liner" as an internal lining in (heating/ventilation/air conditioning) duct system with the black woven glass cloth facing the air stream surface. Install in accordance with the manufacturer's detail and specification.

PHYSICAL PROPERTIES

Rval (m ² .K/W)	Thickness (mm)	Length (mm)	Width (mm)	Density (kg/m ³)	k-value (W/m.K)	NRC Val
0.69	25	10 000	1200	24	0.036	0.85
1.32	50	10 000	1200	18	0.038	-

Typical values

HANDLING & STORAGE

Store product under cover and in dry conditions. Store flat. Handle with care, especially on the edges and corners, which can be damaged if subject to sharp or heavy impact. Do not apply excessive pressure, for example by standing or sitting on the product, as permanent damage may be caused.



ISOVER reserves the right to alter or amend product specification without notice. The information given in this publication is correct to the best of our knowledge at the time of publication. Whilst Isover will endeavour to ensure publications are up to date, it is the users' responsibility to check with us that it is correct prior to use.